



HIGHNO 5.0 – COAXIAL POWDER NOZZLE

Precise, efficient and suitable for series production

With the coaxial powder nozzles, the powder is injected into the molten bath through a conical annular gap. A fine powder gas jet focus can be achieved through the conical powder feed. As a result, high powder efficiency is achieved even with narrow coating traces of less than one millimeter.

The monolithic design of the nozzle tip module, consisting of an inner and an outer cone, is pre-assembled using appropriate shape and position tolerances and replaced without the need for manual adjustment.

- **Plug-and-Play-Solution** for the industry
- **Conversion on site** in a short time (replacement of the nozzle tips in less than 2 minutes)
- **Reproducible changing** of the nozzle tips (qualification of the nozzle tip modules possible)
- **Suitable for high laser power** through indirect water cooling
- **High wear resistance** thanks to special coatings
- **Different gap dimensions** for high variability

Contact

HD Special Optics for Laser Technology

Harald Dickler, Master Toolmaker
Sadagopan Tharmakulasingam, M. Ing.
Telephone +49 2451 6169 989

Technical Specifications

Design	monolithic
Laser beam source	Solid state, diode, gas
Laser power	Up to 12 kW (This information depends on the source and application.)
Weight	max. 1 kg
Stand-Off	13 - 16 mm
Powder particle size	20 - 50 μm , 50 - 100 μm (recommended)
Powder gas jet focus	2.0 mm at 3 g/min
Possible track widths	2.5 - 7 mm
Max. powder mass flow	200 g/min
Cooling	direct water cooling 1-3 l/min at 18 - 20 °C
Surface	<ul style="list-style-type: none"> • uncoated • special coatings for high wear resistance
Max. powder efficiency	up to 90% with track widths of 2.5 mm and a grain size of 20 - 50 μm
Connection	customer specification